



MODEL		<b>XBST05</b>
Drive Type		Stand-on
Steering		Powerd
Load Capacity	(Kgs.)	500
Max Lift Height	H2 (mm)	6500
Lowerd Height	H1 (mm)	250
Drive unit width	DW (mm)	1000±10
Platform Length	FL(mm)	1500
Platform Width	W(mm)	1000
Inside Usable Platform	(mm)	870WX1280L
Overall Length	A1 (mm)	2345±10
Ground Clearance	G(mm)	80
Intersecting Aisle	(mm)	1500x2500
Steering Handle On Platform		
Tyres/Wheels	Type	Polyurethane
Load Wheels Size(Tandem Type)	(mm) PU	Ø150X50
Drive Wheels Size	(mm) PU	Ø230X70
Castor spring loaded	(mm) PU	Ø125X60
Drive Motor	KW	1.3
Steering Motor	W	400
Lift Motor	KW	3
Battery	V/AH	24/225
Brake		EM/Regen
Charger make		sinus/Rege/Sandev
Charger Type		Transformer
Drive Speed Laden/UnLade		7/7%
Lift Speed		0.17/0.17 m/s
Gradient Without/with load		0.17/0.17 m/s
Finish Colour		RAL1004
<b>Safety Accessories</b>		
Horn		Yes
Rev.Horn		Yes
Flasher with buzzer		Yes
Foot Switch		Yes
Support Tie Rod		Yes
Emergency Cut-off		Yes