



Joist hand pallet truck with 2500 kgs capacity, offers users with simple, economic and reliable handling equipment. Hydraulic pump passed the strict test, convenient design for repair or maintenance, chasis is with high strength and durable.

FEATURES:

- Cast steel pump
- 3 & 4mm fork thickness
- Full Stiffner
- Double Nylon, Wheel size: 180*50+80*70mm
- New fork with pressed rib
- Square rubber handle
- 85mm lowered height
- With front guide roller
- With Exit pallet guide roller(wheel fork)
- Adjustable push rods
- With foot pedal release — (Bearing cover & Rocker arm cover & 12 grease fittings)
- Double Nylon, Wheel size: 180*50+80*70mm
- New fork with pressed rib
- Square rubber handle
- 85mm lowered height
- With front guide roller
- With Exit pallet guide roller(wheel fork)
- Adjustable push rods
- With foot pedal release — (Bearing cover & Rocker arm cover 12 grease fittings)more secure security
- Steering chassis design coupled with rubber inflatable wheel, easy to move and flexible
- Power supply voltage selection AC industrial electricity AC380V

TECHNICAL SPECIFICATION:

Feature	Model		
	capacity	kg	2500
	pump type		Intergrated
Wheel	wheel(drive/load) Type		Nylon
	size of steering wheel	mm	180*50
	size of Loading wheel (single wheel)	mm	80*93
	size of Loading wheel (double wheel)	mm	80*70
Dimensions	lifting height	mm	115
	max. fork lifting height	mm	200
	Lowered height of fork	mm	85
	fork outside distance	mm	685
	fork length	mm	1220
	fork width	mm	160
	steel thickness(after painting)	mm	4
	weight	kg	66.8-71

Feature	Model		ND-2500-1150-550-85X
	capacity	kg	2500
	pump type		Intergrated
Wheel	wheel(drive/load) Type		Nylon
	size of steering wheel	mm	180*50
	size of Loading wheel(single wheel)	mm	80*93
	size of Loading wheel(double wheel)	mm	80*70
Dimensions	li?ing height	mm	115
	max. fork li?ing height	mm	200
	Lowered height of fork	mm	85
	fork outside distance	mm	550
	fork length	mm	1150
	fork width	mm	160
	steel thickness(a?er pain?ng)	mm	3
	weight	kg	59.5-62.5